


Industrial Glass - [Couplings](#) - Adaptor Bellow Flanges

Adaptor bellow flange are used to fit a bellow to a flange having different bolt configuration. These flanges are made of cast iron and are supplied with a split ring. These are particularly used to fit a bellow with a non-glass equipment like Glass-lined Reactor etc. These are used in FBF,VBF type PTFE bellows. Adaptor bellow flanges are generally supplied undrilled. However, if specified, these can be supplied drilled as per "Table E", "Table F" and "ASA150" standards.



Undrilled flanges						Drilled to Table E		
Cat.Ref.	DN	D	D1	D2	L	Cat.Ref.	pcd	n x dØ
BFA1*	25	115	43	51	7	BFA1/E1	82	4 x 12Ø
BFA1.5*	40	150	58	66	7			
BFA2*	50	165	70	81	7	BFA1.5/E	98	4 x 16Ø
BFA3*	80	200	101	112	7			
BFA4*	100	220	134	148	8	BFA2/E	114	4 x 16Ø
BFA6*	150	285	186	196	8			
BFA9*	225	395	260	282	8	BFA3/E	146	4 x 16Ø
BFA12	300	445	342	363	10			

Drilled to Table F			Drilled to ASA 150		
Cat.Ref.	pcd	n x dØ	Cat.Ref.	pcd	n x dØ
BFA1/F	87	4 x 16Ø	BFA1/A	79	4 x 16Ø
BFA1.5/F	105	4 x 16Ø	BFA1.5/A	98	4 x 16Ø
BFA2/F	127	4 x 16Ø	BFA2/A	121	4 x 19Ø
BFA3/F	165	8 x 16Ø	BFA3/A	152	4 x 19Ø
BFA4/F	190	8 x 16Ø	BFA4/A	190	8 x 19Ø
BFA6/F	260	12 x 19Ø	BFA6/A	241	8 x 19Ø
BFA9/F	356	12 x 23Ø	BFA9/A	298	8 x 19Ø
BFA12/F	438	12 x 23Ø	BFA12/A	432	12 x 23Ø

* marked items are available fast.

